

5" Coaxial Ceiling Speaker (2.5W/5W/10W/20W) FCS-420H

Feature:

- ✓ Commercial public address system ceiling speaker with transformer.
- ✓ Hi-fi range coaxial ceiling loudspeaker with fire dome.
- ✓ Ideal for school, restaurant, hotel, train station & airport BGM and speech use.
- ✓ Rated power output 2.5W/5W/10W/20W at 100V.
- ✓ 5" coaxial PP driver unit with 0.75" tweeter
- ✓ Line input 100V or 70V & 8 Ω .
- ✓ ABS enclosure, metal grille and metal back can in white.
- ✓ Flush mount in-ceiling quick and secure installation.
- ✓ Wide dispersion rang installation PA loudspeaker.



Specification:

Model	FCS-420H
Description	5" Coaxial Ceiling Speaker
Rated Power Output	2.5W/5W/10W/20W
Line Input	100V or 70V & 8 Ω
Frequency Response	100-20KHz
SPL(@1W/m)	85dB
Speaker Unit	5" coaxial PP driver with 0.75" tweeter
Cutout Size	168mm
Dimension	Φ203 x145mm
Material	ABS enclosure, metal grille and metal back can in white
Mounting Way	Flush mount in-ceiling quick and secure installation
Weight	1.4kg

Side View & Dimension:



SPL VS Angle & SPL VS Frequency Diagrams:

